

United States Patent [19]

Yoshimoto et al.

[11] Patent Number:

5,250,932

[45] Date of Patent:

Oct. 5, 1993

[54]	LIQUID	CRYSTAL.	DISPLAY	DEVICE
LOT.		CILLOIME		

[75] Inventors: Hataaki Yoshimoto, Chiba; Katsuhiro

Ito, Ichihara, both of Japan

[73] Assignee: Ube Industries, Ltd., Yamaguchi,

Japan

[*] Notice: The portion of the term of this patent

subsequent to Dec. 3, 2008 has been

disclaimed.

[21] Appl. No.: 764,233

[22] Filed: Sep. 23, 1991

Related U.S. Application Data

[63] Continuation of Ser. No. 334,640, Apr. 7, 1989, Pat. No. 5,070,326.

Į.	30]	For	eign	Applicati	on Priority Data
	Apr. 13,	1988	[JP]	Japan	63-89224
	Jun. 6,	1988	[JP]	Japan	63-138870

Ju	ın. 8, 1988	[JP] Japan	***************************************	63-139438
[51]	Int. Cl.5	***************************************		G09G 3/36

[56] References Cited

U.S. PATENT DOCUMENTS

4,233,603	11/1980	Castleberry .
4,403,217	9/1983	Becker et al
4,435,047	3/1984	Ferguson .
4,535,327	8/1985	Hareng et al.
4,632,514	12/1986	Ogawa et al
4,693,560	9/1987	Wiley .

FOREIGN PATENT DOCUMENTS

83/01016 WO86/05282	8/1985 9/1985 6/1981 3/1983 9/1986	European Pat. Off European Pat. Off France . Japan . PCT Int'l Appl PCT Int'l Appl
	3/1988	PCT Int'l Appl

OTHER PUBLICATIONS

"A 5×7, Varistor-Controlled LC Matrix Display", Castleberry et al., SID 82 Digest. pp. 246-247. Patent Abstracts of Japan, Unexamined Applications, P. Field, vol. 11, No. 208, Jul. 7, 1987:Kokai No. 62-28712 (Matsushita Electric).

Primary Examiner—Jeffery Brier Attorney, Agent, or Firm—Finnegan, Henderson, Farabow, Garrett & Dunner

[57] ABSTRACT

An LCD device having an improved contrast, able to be operated by a matrix drive, and having a large display area, comprises a pair of transparent first and second bases; picture element electrodes arranged on the first base; signal lines arranged adjacent to the picture element electrode; non-linear elements consisting of varistor particle layers forming bridges between the picture element electrodes and the signal lines; scanning electrodes arranged on the second base; and a liquid crystal material layer located between the picture element electrodes and the scanning electrodes the liquid crystal material being dispersed in a polymeric matrix to form, for example, a NCAP system.

20 Claims, 11 Drawing Sheets

